

Table 30.

Distribution of pipe stems by bore diameter. (Ratios given are the number of specimens per 10 square feet of excavated area within the structure.)

	3/64"	4/64"	5/64"	6/64"	Total	Mean of Sample ¹	Standard Deviation	Ratio
Casemates								
North	4	795	54	1	854	4.06	.263	26.69
West		42	10		52	4.20	.397	13.00
Southwest	1	1,075	141		1,217	4.11	.322	121.70
Southeast		38	6	1	45	4.18	.411	30.00
East		203	28	1	232	4.13	.349	21.09
Barracks								
East	2	69	19		90	4.19	.447	6.38
West		372	32		404	4.08	.270	31.81
Guardhouse	6	2,775	387	4	3,172	4.12	.337	264.33
Headquarters		16	6		22			3.38
Parade Ground	2	483	79		564	4.14	.354	62.66
Bombproofs								
Northeast		57	6		63	4.10	.293	11.45
Northwest		48	11		59	4.19	.392	12.04
Southwest		5	4	2	11			2.00
Bakehouse		3	2		5			
Ditch		61	10	1	72	4.11	.363	2.48
Ravelin		56	8		64	4.13	.333	14.22
East Scarp		152	21	1	174	4.13	.356	25.97
Sally Port		129	20		149	4.13	.342	17.33
Total	15	6,379	844	11	7,249	4.12	.333	37.04

¹ In 64th inches.